

ADA093996

NOC

# SURFACE CURRENTS.

EAST CENTRAL INDIAN OCEAN  
INCLUDING THE EAST  
INDIAN ARCHIPELAGO (INDONESIA).



AUG ~~EST~~ 1977

REPRINTED 1980

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

NAVAL OCEANOGRAPHIC OFFICE  
NSTL STATION MISSISSIPPI 39522

**Best  
Available  
Copy**

## **ABSTRACT**

THIS ATLAS, AND THE SERIES OF WHICH IT IS A PART, IS COMPUTER GENERATED AND AUTOMATICALLY PLOTTED. IT MAKES AVAILABLE TO THE USER THE MOST RECENT SURFACE CURRENT DATA COLLECTED AND WILL BE UPDATED WHENEVER SUFFICIENT AMOUNTS OF DATA ARE ADDED TO THE DATA FILE. THIS AND THE OTHER ATLASES ARE BASED ON A VAST QUANTITY OF DATA AS COMPARED TO THE PREVIOUS MANUALLY-COMPILED EDITIONS PRINTED IN THE MID-THIRTIES.

THE SURFACE CURRENT INFORMATION IS BASED MAINLY ON SHIP DRIFT, WHICH IS THE DIFFERENCE BETWEEN THE DEAD RECKONING POSITION AND THE POSITION DETERMINED BY ANY TYPE OF NAVIGATIONAL FIX. THIS DIFFERENCE DESCRIBES THE DIRECTION AND SPEED OF THE CURRENT.

#### ACKNOWLEDGMENTS

Messrs. Raymond J. Beauchesne\* and William E. Boisvert made major contributions to this atlas.


---

\*Mr. Beauchesne presently is employed by the Bureau of Naval Personnel.

## FOREWORD

THIS ATLAS, ONE IN A SERIES OF 43 REGIONAL SURFACE CURRENT ATLASES, IS PRODUCED TO FULFILL A NEED OF NAVY PLANNING STAFFS AND THE SCIENTIFIC AND INDUSTRIAL COMMUNITIES FOR THE LATEST AVAILABLE OCEAN SURFACE CURRENT DATA. THESE ATLASES ADD TO THE WEALTH OF NAUTICAL INFORMATION UPON WHICH OPERATIONAL PLANNING, NAVIGATIONAL SAFETY, AND SHIPPING ECONOMY DEPEND. RAPID PRODUCTION AND WIDE DISSEMINATION OF THIS ATLAS ARE MADE POSSIBLE BY THE LATEST COMPUTER TECHNIQUES.

THE CONSTANT IMPROVEMENT IN THE QUALITY OF SURFACE CURRENT DATA RECEIVED OVER THE YEARS IS MADE POSSIBLE LARGELY BY THE MORE THOROUGH REPORTS OF VOLUNTARY OBSERVERS IN RECENT YEARS. THE DEFENSE MAPPING AGENCY, THE OCEANOGRAPHIC OFFICE, AND THE USER OF THE ATLASES RELY ON THE PERSONAL OBSERVATIONS OF THE MAN WHO HAS "BEEN THERE." MARINERS, IN REPORTING THEIR OBSERVATIONS, RENDER A SERVICE NOT ONLY TO THEMSELVES BUT ALSO TO ALL "WHO GO DOWN TO THE SEA IN SHIPS." WITH THE ADVENT OF NUCLEAR POWER, ELECTRONIC NAVIGATION AIDS, AND 300,000-TON SHIPS, UP-TO-DATE, RAPIDLY DISSEMINATED ENVIRONMENTAL AND NAVIGATIONAL INFORMATION HAS BECOME INCREASINGLY IMPORTANT.

  
JOHN R. McDONNELL  
Captain, U.S. Navy  
Commander

Accession For	
NTIS GRA&I	
DTIC TAB	
Unannounced	
Justification.	
By _____	
Distribution/	
Availability	
Dist	Avail and Special
<b>A</b>	


## SURFACE CURRENT ATLASES

THIS SERIES OF COMPUTERIZED ATLASES REPLACES THE OLD HYDROGRAPHIC OFFICE ATLASES OF SURFACE CURRENTS (HOP 566, 568, 569, 570) WHICH WERE MANUALLY COMPILED FROM DATA OBTAINED DURING THE PERIOD 1903 - 1934. THESE NEW ATLASES CONFORM TO THE STANDARD NAVY OCEAN AREA AND REGION INDEX LIMITS SHOWN BELOW: e.g., NOO SP 1402-NP 10 COVERS NORTH PACIFIC REGION 10° EAST OF THE PHILIPPINES.

AS AMOUNTS OF NEW DATA WA

THESE GRAPHICS MAY  
AREAS AS THE NORTH SEA, P  
CURRENTS ARE STRONGLY TID  
PREDICTABLE HOURLY CHANGES

RECENT IMPROVEMENTS IN THE DATA FILE ASSURE THE INCLUSION OF THE LATEST, HIGH-QUALITY SURFACE CURRENT DATA AVAILABLE. THE FILE NOW CONTAINS MORE THAN 4,200,000 OBSERVATIONS AND A GENERAL UPDATE OF THE FILE WILL BE MADE



## SURFACE CURRENT ATLASES


THE OLD HYDROGRAPHIC OFFICE  
WHICH WERE MANUALLY  
1934. THESE NEW ATLASES  
INDEX LIMITS SHOWN BELOW:  
10° EAST OF THE PHILIPPINES.

AS AMOUNTS OF NEW DATA WARRANT, MOST LIKELY EVERY 12 - 18 MONTHS.

THESE GRAPHICS MAY NOT BE TRULY REPRESENTATIVE OF THE ACTUAL FLOW IN SUCH  
AREAS AS THE NORTH SEA, PERSIAN GULF, GULF OF THAILAND, AND YELLOW SEA WHERE  
CURRENTS ARE STRONGLY TIDAL. FOR SUCH AREAS, OTHER SOURCES DESCRIBING  
PREDICTABLE HOURLY CHANGES OF TIDAL CURRENTS SHOULD BE CONSULTED.

CONCLUSION OF THE LATEST,  
THE NOW CONTAINS MORE  
THE FILE WILL BE MADE

### INDEX



## Introduction

The Surface Current Data File, from which these atlases are derived, consists primarily of over four million ship set and drift observations. These data were collected by the Netherlands, Japan, Britain, France, and the United States. The file is supplemented by several thousand Geomagnetic Electrokinetograph (GEX) observations, mostly Japanese. The file spans the period from the early 1850's to the present. The earliest observations were collected by the Netherlands and Great Britain; those of the 1960's through the present are primarily United States data.


## General Quality

The quality of this data file is considered high for this type of derived value. The data have been carefully screened for duplication; observations taken under adverse conditions (i.e. high winds and waves, time between observations greater than 12 hours) have been eliminated when warranted. Consideration was given to the reliability of the observer; doubtful shipboard computations of set and drift were edited; and observations with erroneous locations (mostly observations on land) have been eliminated. The accepted data are considered most useful when used collectively as in summaries where a number of observations show trends.

## General Observation Technique

The set (direction) and drift (speed) are computed by the navigator from the difference between the dead reckoning (DR) position and the position determined by any type of navigational fix. The drift can be determined along any straight line track and includes all factors which cause changes in the DR position. When a fix is obtained, the current set (direction) is FROM the DR position TO the fix; the drift (speed) is equal to the distance in nautical miles between the DR and the fix, divided by the number of hours since the last fix. For successive observations, the TO POSITION of one observation becomes the FROM POSITION of the next observation.

Because the influence of current may vary along a ship's track, the MEAN POSITION of the track is assigned as the geographic location of the current observation. An example of a current computation is shown in the figure below.




EXAMPLE OF A SURFACE CURRENT (SHIP'S DRIFT) OBSERVATION

## Data Presentation


The following legend shows two types of surface current presentations by 1° quadrangle, type 1 with 12 or more observations and type 2 with fewer than 12 observations. Where there are 11 or fewer observations within a 1° quadrangle, the total number of observations is shown within the 90° quadrant containing the observations.

## LEGEND

### TYPE 1



### TYPE 2



A NUMBER OF CALMS (INCLUDED IN TOTAL OBSERVATIONS).

B TOTAL OBSERVATIONS (999 ALSO USED FOR 1000 OR MORE OBSERVATIONS).

C MEAN SPEED (0.8 KNOT) FOR ALL OBSERVATIONS.


D VECTOR RESULTANT DIRECTION (°T) FOR ALL OBSERVATIONS.

E PERCENT FREQUENCIES (571 PRIMARY DIRECTION, 231 SECONDARY DIRECTION).

F MEAN SPEEDS (1.0 KNOT PRIMARY DIRECTION, 0.6 KNOT SECONDARY DIRECTION).


G NUMBER OF OBSERVATIONS BY QUADRANT.

If there are 12 or more observations by vector resultants as follows:




(1) Persistent Current - 60 percent or more of all observations fall within a 45° sector of the 8-point compass.

(2) Prevailing Current - all observations fall within a 45° sector.



(4) Bizonal Flow - Practically all observations are concentrated in opposite pairs of 45° sectors, and one pair contains at least 80 percent as many observations as the opposite pair. This generally indicates variability that occurs in zones of entrainment between opposing currents (see examples A and B, quadrangles 1, 2, and 3).








If there are 12 or more observations in a 1° quadrangle, the surface current is depicted by vector resultants as follows:

onsists primarily collected by the is supplemented mostly Japanese. earliest observa- 1960's through

ved value. The under adverse: er than 12 hours) e liability edited; and ob- been eliminated. in summaries:



on the difference y any type of track and includes ined, the current is equal to the number of hours e observation



AN POSITION OF tion. An example

(1) Persistent Current - 60 percent or more of all observations fall within a 45° sector of the 8-point compass.

(2) Prevailing Current - 70 percent or more of all observations fall within two adjacent 45° sectors.


(3) Primary Current with Secondary Direction - (a) Primary Current - 50 percent or more of all observations fall within three adjacent 45° sectors.

(b) Secondary Direction - 20 percent or more of all observations fall within a 45° sector, and the two resultant vector directions are separated by more than 90° of arc.



(4) Bizonal Flow - Practically all observations are concentrated in opposite pairs of 45° sectors, and one pair contains at least 80 percent as many observations as the opposite pair. This generally indicates variability that occurs in zones of entrainment between opposing currents (see examples A and B, quadrangles 1, 2, and 3).

(5) Variable Current - The 45° sector with most observations has less than 25 percent of all observations; direction is indeterminate.



TOTAL OBSERVATIONS).

USED FOR 1000' OR


OBSERVATIONS.

(T) FOR ALL OBSERVATIONS.


ARY DIRECTION, 23%


DIRECTION, 0.6 KNOT

DRANT.





SUMMER - JAN, FEB, MAR







AUTUMN - APR, MAY, JUN














SPRING - OCT, NOV, DEC

4









DISTRIBUTION LIST

NAVY

CINCPACFLT (02M)  
COMTHIRDFLT  
COMSEVENTHFLT  
COMSUBPAC  
COMNAVAIRPAC  
COMPATWINGSPAC  
PATWINGSPAC DET ADAK  
PATWING 1  
COMNAVSURFPAC  
DIRNAVOCEANMET  
FLENUMWEACEN  
FLEWEACEN GUAM  
FLEWEACEN PEARL  
NAVWEASERVFAC SAN DIEGO  
NAVWEASERVFAC YOKOSUKA  
NWS D ASHEVILLE  
NWS D ADAK  
NWS D AGANA  
NWS D ATSUGI  
NWS D KADENA  
NWS D MISAWA

OTHER GOVT.

NOAA/NODC  
NOAA/NCC

PRIVATE

AMAX EXPLORATION INC.

FOREIGN

HYDROGRAPHER/R.A.N.  
DEPT. TRANSPORTATION/AUSTRALIA

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER N60 SP1404-IN5	2. GOVT ACCESSION NO. AD A093 976	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SURFACE CURRENTS EAST CENTRAL INDIAN OCEAN INCLUDING THE EAST INDIAN ARCHIPELAGO (INDONESIA)		5. TYPE OF REPORT & PERIOD COVERED FINAL
7. AUTHOR(s) Naval Oceanographic Office NSTL Station, MS 39522		6. PERFORMING ORG. REPORT NUMBER
8. PERFORMING ORG. ZATION NAME AND ADDRESS Naval Oceanographic Office		9. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE August 1977
		13. NUMBER OF PAGES 14
		14. SECURITY CLASS (for this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (for this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Surface Currents East Central Indian Ocean East Indian Archipelago		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This atlas, and the series of which it is a part, is computer generated and automatically plotted. It makes available to the user the most recent surface current data collected and will be updated whenever sufficient amounts of data are added to the data file. This and the other atlases are based on a vast quantity of data as compared to the previous manually-compiled editions printed in the mid-thirties.		

DD FORM 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-010-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20. Cont.

The surface current information is based mainly on ship is the difference between the dead reckoning position and determined by any type of navigational fix. This difference the direction and speed of the current.

SECURITY CLASSIFICATION OF THIS PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NO.	2. RECIPIENT'S CATALOG NUMBER
3. TYPE OF REPORT & PERIOD COVERED	4. PERFORMING ORG. REPORT NUMBER
5. CONTRACT OR GRANT NUMBER(s)	6. PROGRAM ELEMENT PROJECT TASK AREA & WORK UNIT NUMBERS
7. REPORT DATE	8. REPORT TYPE
9. NUMBER OF PAGES	10. SECURITY CLASS. (of this report)
11. DECLASSIFICATION/DOWNGRADING SCHEDULE	
12. LIMITATION	
13. ABSTRACT	
14. PART, IS COMPUTER GENERATED	
15. TO THE USER THE MOST RECENT	
16. WHENEVER SUFFICIENT AMOUNTS	
17. THE OTHER ATLASES ARE BASED ON	
18. ILLUSTRATIONS MANUALLY-COMPILED	

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20. Cont.

The surface current information is based mainly on ship drift, which is the difference between the dead reckoning position and the position determined by any type of navigational fix. This difference describes the direction and speed of the current.